

Artykuł	Nr. kat.	Wymiar
Rura homogeniczna PP-R 20° C/2,0 MPa • 70° C/1,0 MPa	 <b>W 8200</b>	20
Rura wielowarstwowa stabilizowana folią aluminiową <b>PP-R CT</b> /Alu/PP-R 20° C/2,0 MPa • 70° C/1,0 Mpa	 <b>W 8215</b>	20
		25
		32
		40
		50
Kolanko 45° nypłowe	 <b>8040</b>	20
		25
		32
		40
Kolanko 45°	 <b>8041</b>	20
		25
		32
		40
Kolanko 90°	 <b>8090</b>	20
		25
		32
		40
		50
Kolanko 90° nypłowe	 <b>8092</b>	20
		25
		32
		40
Trójnik	 <b>8130</b>	20
		25
		32
Trójnik redukcyjny	 <b>8130 red</b>	25-20-25
		32-20-32
		32-25-32
		40-20-40
		40-25-40
		50-40-50

Artykuł		Nr. kat.	Wymiar
Redukcja		8243	25-20
			32-20
			32-25
			40-20
			40-32
			50-40
Mufa		8270	20
			25
			32
			40
			50
Kolanko z gwintem wewnętrznym		8090 g	20 x 1/2"
Kolanko z gwintem zewnętrznym		8092 g	20 x 1/2"
Złączka z gwintem zewnętrznym		8243 g	20 x 1/2"
			25 x 1/2"
			25 x 3/4"
			32 x 1"
Złączka z gwintem wewnętrznym		8270 g	20 x 1/2"
			25 x 1/2"
			25 x 3/4"
			32 x 1"
Kolanko z gwintem wewnętrznym i uchwytem		8472 g	20 x 1/2"
Obejmy do rur (stalowe)		8500	d 20 ( 1/2" )
			d 25 ( 3/4" )
			d 32 ( 1" )
			d 40 ( 1.1/4" )
			d 50 ( 1.1/2" )
Uchwyt do rur GW (plast)		8503	d 20
			d 25
			d 32
			d 40